

COMMAND[®]

WALLCOVERINGS



VIA

Physical Properties

Weight: Type II 20 oz
Content: 100% Vinyl
Backing: Osnaburg
Width: 52/54"
Repeat: Random Reversible

Performance:

Fire Rating: Class A, ASTM E84
Europe CE Fire Tested
Color Fastness UK Test Result: BS2782-Pass
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)
NSF 342

Product contains up to 40% recycled content
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA
Printed with Solvent-Free Inks
This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA

Available in 18 Colorways

CM96-2048 Pearl	CM96-2057 Sea Grass
CM96-2049 Manilla	CM96-2058 Nutmeg
CM96-2050 Mica	CM96-2059 Pacific
CM96-2051 Buff	CM96-2060 Kelp
CM96-2052 Latte	CM96-2061 Tappas
CM96-2053 Flint	CM96-2062 Purple
CM96-2054 Dove	CM96-2063 Wheat
CM96-2055 Rope	CM96-2064 Barn Red
CM96-2056 Venetian	CM96-2065 Charcoal

